

Multiple Internal SATA to eSATA Low Profile PCI

User Manual

English



LINDY No. 70531

www.LINDY.com





© LINDY ELECTRONICS LIMITED & LINDY-ELEKTRONIK GMBH - FIRST EDITION (June 2006)

1. Introduction

Ideal Low Profile PCI Converter for Mother board Internal SATA

Multiple Ports to External eSATA or Multilane 4x connection

Install this PCI board inside of your computer and make your Motherboard internal onboard SATA ports have 2Port eSATA or Multilane 4X External Serial ATA connection to external SATA Device.

Supports Low Profile PCI Form Factor.

1.1.Features

- Supports High Speed Transfer Rate of SATA II 3Gbps and SATA 1.5Gbps
- For eSATA Dual Ports ----- Has eSATA shielding and durable connectors for External connection
- For Multilane 4 Ports ----- Has Type 4x Multilane SATA connector (*Cross-Over Pinouts*) with thumbscrews for External connection
- Low Profile PCI Form Factor
- Includes 2 Brackets (Low profile PCI and Regular size PCI Brackets)
- Two or Four LED Pin Headers for device accessing

2. Installation

- Step 1. Screw the PCI Bridge board to the available slot
- Step 2. Connect SATA data connectors (P2 & P4 or P1 ~ P4) to SATA Hard drives



FC (E

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operations.